

Package: CopernicusMarine (via r-universe)

September 7, 2024

Type Package

Title Search Download and Handle Data from Copernicus Marine Service Information

Version 0.2.3.002

Date 2024-04-10

Author Pepijn de Vries [aut, cre, dtc] (0000-0002-7961-6646)

Maintainer Pepijn de Vries <pepijn.devries@outlook.com>

Description Subset and download data from EU Copernicus Marine Service Information: <<https://data.marine.copernicus.eu>>. Import data on the oceans physical and biogeochemical state from Copernicus into R without the need of external software.

Depends R (>= 4.1.0)

Imports crayon, dplyr, htr2, leaflet, purrr, readr, rlang, rvest, sf, stringr, tidyr, utils, xml2

Suggests lifecycle, ncmeta, stars, testthat (>= 3.0.0)

URL <https://github.com/pepijn-devries/CopernicusMarine>,
<https://pepijn-devries.github.io/CopernicusMarine/>

BugReports <https://github.com/pepijn-devries/CopernicusMarine/issues>

License GPL (>= 3)

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

Config/testthat/edition 3

Roxygen list(markdown = TRUE)

Collate 'CopernicusMarine-package.r' 'cms_cite_product.r'
'cms_download_stac.r' 'cms_login.r' 'cms_download_subset.r'
'cms_list_stac_files.r' 'cms_product_details.r'
'cms_product_metadata.r' 'cms_product_services.r'
'cms_products_list.r' 'cms_stac_properties.r' 'cms_wmts.r'

```
'copernicus_cite_product.r' 'copernicus_download_motu.r'
'copernicus_login.r' 'copernicus_product_details.r'
'copernicus_product_metadata.r' 'copernicus_products_list.r'
'ftp.r' 'generics.r' 'import.r' 'wms.r'
```

Repository <https://pepijn-devries.r-universe.dev>

RemoteUrl <https://github.com/pepijn-devries/CopernicusMarine>

RemoteRef master

RemoteSha ea11f2317aa47e7a9e7f8f95f94bfb4910cfef9

Contents

addCopernicusWMSTiles	2
cms_cite_product	4
cms_download_stac	5
cms_download_subset	6
cms_login	8
cms_products_list	9
cms_product_details	10
cms_product_metadata	11
cms_product_services	12
cms_wmts_details	12
copernicus_cite_product	14
copernicus_download_motu	15
copernicus_ftp_list	17
copernicus_login	18
copernicus_products_list	19
copernicus_product_details	20
copernicus_product_metadata	21
copernicus_product_services	22
copernicus_wms2geotiff	23
copernicus_wmts_details	24
Index	26

addCopernicusWMSTiles *Add Copernicus Marine WMS Tiles to a leaflet map*

Description

[Deprecated] Create an interactive map with `leaflet::leaflet()` and add layers of Copernicus marine WMS data to it.

Usage

```
addCopernicusWMSTiles(
  map,
  product,
  layer,
  variable,
  options = leaflet::WMSTileOptions(format = "image/png", transparent = TRUE),
  ...
)
```

Arguments

map	A map widget object created from <code>leaflet::leaflet()</code>
product	An identifier (type character) of the desired Copernicus marine product. Can be obtained with <code>copernicus_products_list</code> .
layer	The name of a desired layer within a product (type character). Can be obtained with <code>copernicus_product_details</code> .
variable	The name of a desired variable in a specific layer of a product (type character). Can be obtained with <code>copernicus_product_details</code> .
options	Passed on to <code>leaflet::addWMSTiles()</code> .
...	Passed on to <code>leaflet::addWMSTiles()</code> .

Value

Returns an updated map

Note

WMS functions don't work on systems that don't support GDAL utils

Author(s)

Pepijn de Vries

See Also

Other wms-functions: `copernicus_wms2geotiff()`, `copernicus_wms_details()`

Examples

```
## Not run:
if (interactive()) {
  leaflet::leaflet() |>
    leaflet::setView(lng = 3, lat = 54, zoom = 4) |>
    leaflet::addProviderTiles("Esri.WorldImagery") |>
    addCopernicusWMSTiles(
      product = "GLOBAL_ANALYSISFORECAST_PHY_001_024",
      layer   = "cmems_mod_glo_phy-thetao_anfc_0.083deg_P1D-m",
    )
}
```

```
        variable = "thetao")
    }
## End(Not run)
```

cms_cite_product *How to cite a Copernicus marine product*

Description

[Stable] Get details for properly citing a Copernicus product.

Usage

```
cms_cite_product(product)
```

Arguments

product An identifier (type character) of the desired Copernicus marine product. Can be obtained with [cms_products_list](#).

Value

Returns a vector of character strings. The first element is always the product title, id and doi. Remaining elements are other associated references. Note that the remaining references are returned as listed at Copernicus. Note that the citing formatting does not appear to be standardised.

Author(s)

Pepijn de Vries

See Also

Other product-functions: [cms_product_details\(\)](#), [cms_product_metadata\(\)](#), [cms_product_services\(\)](#), [cms_products_list\(\)](#), [copernicus_cite_product\(\)](#), [copernicus_product_details\(\)](#), [copernicus_product_metadata\(\)](#), [copernicus_products_list\(\)](#)

Examples

```
cms_cite_product("SST_MED_PHY_SUBSKIN_L4_NRT_010_036")
```

cms_download_stac *List and get STAC files for a Copernicus marine product*

Description

[Stable] Full marine data sets can be downloaded using the SpatioTemporal Asset Catalogs (STAC). Use these functions to list download locations and get the files.

Usage

```
cms_download_stac(
  file_tibble,
  destination,
  show_progress = TRUE,
  overwrite = FALSE
)

cms_list_stac_files(product, layer)

cms_stac_properties(product, layer)
```

Arguments

file_tibble	A <code>dplyr::tibble()</code> with in each row the files to be downloaded. Should be created with <code>cms_list_stac_files()</code> .
destination	A character string representing the path location where the downloaded files should be stored.
show_progress	A logical value. When TRUE (default) the download progress will be shown. This can be useful for large files.
overwrite	A logical value. When FALSE (default), files at the destination won't be overwritten when they exist. Instead an error will be thrown if this is the case. When set to TRUE, existing files will be overwritten.
product	An identifier (type character) of the desired Copernicus marine product. Can be obtained with <code>cms_products_list</code> .
layer	The name of a desired layer within a product (type character). Can be obtained with <code>cms_product_details</code> .

Value

In case of `cms_stac_properties` a `dplyr::tibble()` is returned with some product properties, It is used as precursor for `cms_list_stac_files`. In case of `cms_list_stac_files` a `dplyr::tibble()` is returned containing available URLs (for the specified product and layer) and some meta information is returned. In case of `cms_download_stac` an invisible logical value is returned, indicating whether all requested files are successfully stored at the destination path. A list of responses (of class `httr2::response()`) for all requested download links is included as attribute to the result.

Author(s)

Pepijn de Vries

Examples

```
## Not run:
## List some STAC properties for a specific product and layer
cms_stac_properties(
  product      = "GLOBAL_ANALYSISFORECAST_PHY_001_024",
  layer        = "cmems_mod_glo_phy-cur_anfc_0.083deg_P1D-m"
)

## Get the available files for a specific product and layer:
file_tibble <-
  cms_list_stac_files("GLOBAL_ANALYSISFORECAST_PHY_001_024",
                    "cmems_mod_glo_phy-cur_anfc_0.083deg_P1D-m")

dest <- tempdir()

## download the first file from the file_tibble to 'dest'
cms_download_stac(file_tibble[1,, drop = FALSE], dest)

## End(Not run)
```

cms_download_subset *Subset and download a specific marine product from Copernicus*

Description

[Stable] Subset and download a specific marine product from Copernicus. You need to register an account at <https://data.marine.copernicus.eu> before you can use this function.

Usage

```
cms_download_subset(
  username = getOption("CopernicusMarine_uid", ""),
  password = getOption("CopernicusMarine_pwd", ""),
  destination,
  product,
  layer,
  variable,
  region,
  timerange,
  verticalrange,
  overwrite = FALSE
)
```

Arguments

username	Your Copernicus marine user name. Can be provided as options(CopernicusMarine_uid = "my_user_name"), or as argument here.
password	Your Copernicus marine password. Can be provided as options(CopernicusMarine_pwd = "my_password"), or as argument here.
destination	File or path where the requested file will be downloaded to.
product	An identifier (type character) of the desired Copernicus marine product. Can be obtained with cms_products_list .
layer	The name of a desired layer within a product (type character). Can be obtained with cms_product_details .
variable	The name of a desired variable in a specific layer of a product (type character). Can be obtained with copernicus_product_details .
region	Specification of the bounding box as a vector of numerics WGS84 lat and lon coordinates. Should be in the order of: xmin, ymin, xmax, ymax.
timerange	A vector with two elements (lower and upper value) for a requested time range. The vector should be coercible to POSIXct.
verticalrange	A vector with two elements (minimum and maximum) numerical values for the depth of the vertical layers (if any). Note that values below the sea surface needs to be specified as negative values.
overwrite	A logical value. When FALSE (default), files at the destination won't be overwritten when they exist. Instead an error will be thrown if this is the case. When set to TRUE, existing files will be overwritten.

Value

Returns a logical value invisibly indicating whether the requested file was successfully stored at the destination.

Author(s)

Pepijn de Vries

Examples

```
## Not run:
destination <- tempfile("copernicus", fileext = ".nc")

## Assuming that Copernicus account details are provided as `options`
cms_download_subset(
  destination = destination,
  product     = "GLOBAL_ANALYSISFORECAST_PHY_001_024",
  layer       = "cmems_mod_glo_phy-cur_anfc_0.083deg_P1D-m",
  variable    = "sea_water_velocity",
  region      = c(-1, 50, 10, 55),
  timerange   = c("2021-01-01 UTC", "2021-01-02 UTC"),
  verticalrange = c(0, -2)
)
```

```
mydata <- stars::read_stars(destination)

plot(mydata["vo"])

## End(Not run)
```

cms_login

Contact Copernicus Marine login page

Description

[Stable] Contact Copernicus Marine login page and check if login is successful.

Usage

```
cms_login(
  username = getOption("CopernicusMarine_uid", ""),
  password = getOption("CopernicusMarine_pwd", "")
)
```

Arguments

username	Your Copernicus marine user name. Can be provided as options(CopernicusMarine_uid = "my_user_name"), or as argument here.
password	Your Copernicus marine password. Can be provided as options(CopernicusMarine_pwd = "my_password"), or as argument here.

Details

This function will return a logical value indicating if the login is successful. It can be used to test your account details.

Value

Returns a logical value indicating if the login is successful. The response from the login page is returned as an attribute named response.

Author(s)

Pepijn de Vries

Examples

```
## Not run:
## This will return FALSE if you have not set your account details with 'options'.
## If you have specified your account details and there are no other problems,
## it will return TRUE.
copernicus_login()

## End(Not run)
```

cms_products_list *List products available from data.marine.copernicus.eu*

Description

[Stable] Collect a list of products and some brief descriptions for marine products available from Copernicus

Usage

```
cms_products_list(..., info_type = c("list", "meta"))
```

Arguments

...	Allows you to pass (search) query parameters to apply to the list. When omitted, the full list of products is returned.
info_type	One of "list" (default) or "meta". "list" returns the actual list whereas "meta" returns meta information for the executed query (e.g. number of hits).

Value

Returns a tibble of products available from <https://data.marine.copernicus.eu> or a named list when info_type = "meta". Returns NULL in case on-line services are unavailable.

Author(s)

Pepijn de Vries

See Also

Other product-functions: [cms_cite_product\(\)](#), [cms_product_details\(\)](#), [cms_product_metadata\(\)](#), [cms_product_services\(\)](#), [copernicus_cite_product\(\)](#), [copernicus_product_details\(\)](#), [copernicus_product_metadata\(\)](#), [copernicus_products_list\(\)](#)

Examples

```
cms_products_list()

## Query a specific product:
cms_products_list(freeText = "GLOBAL_ANALYSISFORECAST_PHY_001_024")
```

cms_product_details *Obtain details for a specific Copernicus marine product*

Description

[Stable] Obtain details for a specific Copernicus marine product. This can be narrowed down to specific layers and/or variables within the product.

Usage

```
cms_product_details(  
  product,  
  layer,  
  variable,  
  variant = c("", "detailed-v2", "detailed-v3")  
)
```

Arguments

product	An identifier (type character) of the desired Copernicus marine product. Can be obtained with cms_products_list .
layer	The name of a desired layer within a product (type character). Can be obtained with cms_product_details .
variable	The name of a desired variable in a specific layer of a product (type character). Can be obtained with copernicus_product_details .
variant	A character string indicating the type of details that should be returned. Should be one of "" (default), "detailed-v2", or "detailed-v3".

Value

Returns a named list with properties of the requested product.

Author(s)

Pepijn de Vries

See Also

Other product-functions: [cms_cite_product\(\)](#), [cms_product_metadata\(\)](#), [cms_product_services\(\)](#), [cms_products_list\(\)](#), [copernicus_cite_product\(\)](#), [copernicus_product_details\(\)](#), [copernicus_product_metadata\(\)](#), [copernicus_products_list\(\)](#)

Examples

```
cms_product_details("GLOBAL_ANALYSISFORECAST_PHY_001_024")

cms_product_details(
  product = "GLOBAL_ANALYSISFORECAST_PHY_001_024",
  layer   = "cmems_mod_glo_phy-thetao_anfc_0.083deg_P1D-m",
  variable = "thetao"
)
```

cms_product_metadata *Obtain meta data for a specific Copernicus marine product*

Description

[Stable] Collect meta information, such as vocabularies used, for specific Copernicus marine products

Usage

```
cms_product_metadata(product, type = c("list", "xml"))
```

Arguments

product	An identifier (type character) of the desired Copernicus marine product. Can be obtained with cms_products_list .
type	A character string indicating how the data should be returned. Should be one of "list" or "xml".

Value

Returns a named list (when type = "list") with info about the requested product. Returns the same info as `xml_document` (see [xml2::xml_new_document\(\)](#)) when type = "xml". Returns NULL when contacting Copernicus fails.

Author(s)

Pepijn de Vries

See Also

Other product-functions: [cms_cite_product\(\)](#), [cms_product_details\(\)](#), [cms_product_services\(\)](#), [cms_products_list\(\)](#), [copernicus_cite_product\(\)](#), [copernicus_product_details\(\)](#), [copernicus_product_metadata\(\)](#), [copernicus_products_list\(\)](#)

Examples

```
cms_product_metadata("GLOBAL_ANALYSISFORECAST_PHY_001_024")
```

cms_product_services *Obtain available services for a specific Copernicus marine product*

Description

[Deprecated] Obtain an overview of services provided by Copernicus for a specific marine product.

Usage

```
cms_product_services(product)
```

Arguments

product An identifier (type character) of the desired Copernicus marine product. Can be obtained with [cms_products_list](#).

Value

Returns a tibble with a list of available services for a Copernicus marine product.

Author(s)

Pepijn de Vries

See Also

Other product-functions: [cms_cite_product\(\)](#), [cms_product_details\(\)](#), [cms_product_metadata\(\)](#), [cms_products_list\(\)](#), [copernicus_cite_product\(\)](#), [copernicus_product_details\(\)](#), [copernicus_product_metadata\(\)](#), [copernicus_products_list\(\)](#)

Examples

```
cms_product_services("GLOBAL_ANALYSISFORECAST_PHY_001_024")
```

cms_wmts_details *Obtain a WMTS entry for specific Copernicus marine products and add to a leaflet map*

Description

[Stable] Functions for retrieving Web Map Tile Services information for specific products, layers and variables and add them to a leaflet map.

Usage

```

cms_wmts_details(product, layer, variable)

addCmsWMTSTiles(
  map,
  product,
  layer,
  variable,
  tilematrixset = "EPSG:3857",
  options = leaflet::WMSTileOptions(format = "image/png", transparent = TRUE),
  ...
)

cms_wmts_get_capabilities(product, layer, variable, type = c("list", "xml"))

```

Arguments

product	An identifier (type character) of the desired Copernicus marine product. Can be obtained with cms_products_list .
layer	The name of a desired layer within a product (type character). Can be obtained with cms_product_details .
variable	The name of a desired variable in a specific layer of a product (type character). Can be obtained with copernicus_product_details .
map	A map widget object created from leaflet::leaflet()
tilematrixset	A character string representing the tilematrixset to be used. In many cases "EPSG:3857" (Pseudo-Mercator) or "EPSG:4326" (World Geodetic System 1984) are available, but should be checked with cms_wmts_details .
options	Passed on to leaflet::addWMSTiles() .
...	Passed on to leaflet::addWMSTiles() .
type	A character string indicating whether the capabilities should be returned as "list" (default) or "xml" (xml2::xml_new_document()).

Value

`cms_wmts_details` returns a tibble with details on the WMTS service. `cms_wmts_getcapabilities` returns either a list or xml_document depending on the value of type. `AddCmsWMTSTiles` returns a leaflet map updated with the requested tiles.

Author(s)

Pepijn de Vries

Examples

```

cms_wmts_details(
  product = "GLOBAL_ANALYSISFORECAST_PHY_001_024",
  layer   = "cmems_mod_glo_phy-thetao_anfc_0.083deg_P1D-m",

```

```

    variable = "thetao"
  )

  cms_wmts_get_capabilities("GLOBAL_ANALYSISFORECAST_PHY_001_024")

  if (interactive()) {
    leaflet::leaflet() |>
      leaflet::setView(lng = 3, lat = 54, zoom = 4) |>
      leaflet::addProviderTiles("Esri.WorldImagery") |>
      addCmsWMTSTiles(
        product = "GLOBAL_ANALYSISFORECAST_PHY_001_024",
        layer   = "cmems_mod_glo_phy-thetao_anfc_0.083deg_P1D-m",
        variable = "thetao")
  }

```

copernicus_cite_product

How to cite a Copernicus marine product

Description

[Deprecated] Get details for properly citing a Copernicus product.

Usage

```
copernicus_cite_product(product)
```

Arguments

product An identifier (type character) of the desired Copernicus marine product. Can be obtained with [copernicus_products_list](#).

Value

Returns a vector of character strings. The first element is always the product title, id and doi. Remaining elements are other associated references. Note that the remaining references are returned as listed at Copernicus. Note that the citing formatting does not appear to be standardised.

Author(s)

Pepijn de Vries

See Also

Other product-functions: [cms_cite_product\(\)](#), [cms_product_details\(\)](#), [cms_product_metadata\(\)](#), [cms_product_services\(\)](#), [cms_products_list\(\)](#), [copernicus_product_details\(\)](#), [copernicus_product_metadata\(\)](#), [copernicus_products_list\(\)](#)

Examples

```
## Not run:
copernicus_cite_product("SST_MED_PHY_SUBSKIN_L4_NRT_010_036")

## End(Not run)
```

copernicus_download_motu

Subset and download a specific marine product from Copernicus

Description

[Deprecated] The MOTU servers will be discontinued by Copernicus Marine Services. Use [cms_download_subset\(\)](#) instead to download subsets.

Usage

```
copernicus_download_motu(
  username = getOption("CopernicusMarine_uid", ""),
  password = getOption("CopernicusMarine_pwd", ""),
  destination,
  product,
  layer,
  variable,
  output,
  region,
  timerange,
  verticalrange,
  sub_variables,
  overwrite = FALSE
)
```

Arguments

username	Your Copernicus marine user name. Can be provided as options(CopernicusMarine_uid = "my_user_name"), or as argument here.
password	Your Copernicus marine password. Can be provided as options(CopernicusMarine_pwd = "my_password"), or as argument here.
destination	File or path where the requested file will be downloaded to.
product	An identifier (type character) of the desired Copernicus marine product. Can be obtained with copernicus_products_list .
layer	The name of a desired layer within a product (type character). Can be obtained with copernicus_product_details .
variable	The name of a desired variable in a specific layer of a product (type character). Can be obtained with copernicus_product_details .

output	File type for the output. "netcdf" will work in most cases.
region	Specification of the bounding box as a vector of numeric WGS84 lat and lon coordinates. Should be in the order of: xmin, ymin, xmax, ymax.
timerange	[Experimental] A vector with two elements (lower and upper value) for a requested time range. The vector should be coercible to POSIXct.
verticalrange	[Experimental] A vector with two elements (minimum and maximum) numerical values for the depth of the vertical layers (if any).
sub_variables	A vector of names of requested sub variables.
overwrite	A logical value. When FALSE (default), files at the destination won't be overwritten when they exist. Instead an error will be thrown if this is the case. When set to TRUE, existing files will be overwritten.

Value

Returns a logical value invisibly indicating whether the requested file was successfully stored at the destination.

Author(s)

Pepijn de Vries

Examples

```
## Not run:
destination <- tempfile("copernicus", fileext = ".nc")

## Assuming that Copernicus account details are provided as `options`
copernicus_download_motu(
  destination = destination,
  product     = "GLOBAL_ANALYSISFORECAST_PHY_001_024",
  layer       = "cmems_mod_glo_phy-cur_anfc_0.083deg_P1D-m",
  variable    = "sea_water_velocity",
  output      = "netcdf",
  region      = c(-1, 50, 10, 55),
  timerange   = c("2021-01-01", "2021-01-02"),
  verticalrange = c(0, 2),
  sub_variables = c("uo", "vo")
)

mydata <- stars::read_stars(destination)

plot(mydata["vo"])

## End(Not run)
```

copernicus_ftp_list *List and get FTP files for a Copernicus marine product*

Description

[Deprecated] Full marine data sets can be downloaded using the File Transfer Protocol (FTP). Use these functions to list download locations and get the files.

Usage

```
copernicus_ftp_list(  
    product,  
    layer,  
    username = getOption("CopernicusMarine_uid", ""),  
    password = getOption("CopernicusMarine_pwd", ""),  
    recursive = TRUE,  
    subdir = NULL  
)
```

```
copernicus_ftp_get(  
    url,  
    destination,  
    show_progress = TRUE,  
    overwrite = FALSE,  
    username = getOption("CopernicusMarine_uid", ""),  
    password = getOption("CopernicusMarine_pwd", "")  
)
```

Arguments

product	An identifier (type character) of the desired Copernicus marine product. Can be obtained with copernicus_products_list .
layer	The name of a desired layer within a product (type character). Can be obtained with copernicus_product_details .
username	Your Copernicus marine user name. Can be provided as options(CopernicusMarine_uid = "my_user_name"), or as argument here.
password	Your Copernicus marine password. Can be provided as options(CopernicusMarine_pwd = "my_password"), or as argument here.
recursive	A logical value. When TRUE all nested files will be listed.
subdir	A character string of a subdir which will be appended to the obtained ftp address.
url	The URL of the file to be downloaded. Obtain this URL with copernicus_ftp_list .
destination	File or path where the requested file will be downloaded to.
show_progress	A logical value. When TRUE (default) the download progress will be shown. This can be useful for large files.

overwrite A logical value. When FALSE (default), files at the destination won't be overwritten when they exist. Instead an error will be thrown if this is the case. When set to TRUE, existing files will be overwritten.

Value

In case of `copernicus_ftp_list` a tibble is returned containing available URLs (for the specified product and layer) and some meta information is returned. In case of `copernicus_ftp_get` an invisible logical value is returned, indicating whether the requested file is successfully stored at the destination path.

Author(s)

Pepijn de Vries

Examples

```
## Not run:
## Assuming that Copernicus account details are provided as `options`
cop_ftp_files <- copernicus_ftp_list("GLOBAL_OMI_WMHE_heattrp")

destination <- tempdir()

copernicus_ftp_get(cop_ftp_files$url[[1]], destination)

## End(Not run)
```

copernicus_login

Contact Copernicus Marine login page

Description

[Deprecated] This login method is only used by the download methods that are deprecated by Copernicus Marine Services. Use [cms_login\(\)](#) instead.

Usage

```
copernicus_login(
  username = getOption("CopernicusMarine_uid", ""),
  password = getOption("CopernicusMarine_pwd", "")
)
```

Arguments

username Your Copernicus marine user name. Can be provided as `options(CopernicusMarine_uid = "my_user_name")`, or as argument here.

password Your Copernicus marine password. Can be provided as `options(CopernicusMarine_pwd = "my_password")`, or as argument here.

Value

Returns a logical value indicating if the login is successful. The response from the login page is returned as an attribute named response.

Author(s)

Pepijn de Vries

Examples

```
## Not run:  
## This will return FALSE if you have not set your account details with 'options'.  
## If you have specified your account details and there are no other problems,  
## it will return TRUE.  
copernicus_login()  
  
## End(Not run)
```

copernicus_products_list

List products available from data.marine.copernicus.eu

Description

[Deprecated] Collect a list of products and some brief descriptions for marine products available from Copernicus

Usage

```
copernicus_products_list(..., info_type = c("list", "meta"))
```

Arguments

...	Allows you to pass (search) query parameters to apply to the list. When omitted, the full list of products is returned.
info_type	One of "list" (default) or "meta". "list" returns the actual list whereas "meta" returns meta information for the executed query (e.g. number of hits).

Value

Returns a tibble of products available from <https://data.marine.copernicus.eu> or a named list when info_type = "meta". Returns NULL in case on-line services are unavailable.

Author(s)

Pepijn de Vries

See Also

Other product-functions: [cms_cite_product\(\)](#), [cms_product_details\(\)](#), [cms_product_metadata\(\)](#), [cms_product_services\(\)](#), [cms_products_list\(\)](#), [copernicus_cite_product\(\)](#), [copernicus_product_details\(\)](#), [copernicus_product_metadata\(\)](#)

Examples

```
## Not run:
copernicus_products_list()

## Query a specific product:
copernicus_products_list(freeText = "GLOBAL_ANALYSISFORECAST_PHY_001_024")

## End(Not run)
```

copernicus_product_details

Obtain details for a specific Copernicus marine product

Description

[Deprecated] Obtain details for a specific Copernicus marine product. This can be narrowed down to specific layers and/or variables within the product.

Usage

```
copernicus_product_details(product, layer, variable)
```

Arguments

product	An identifier (type character) of the desired Copernicus marine product. Can be obtained with copernicus_products_list .
layer	The name of a desired layer within a product (type character). Can be obtained with copernicus_product_details .
variable	The name of a desired variable in a specific layer of a product (type character). Can be obtained with copernicus_product_details .

Value

Returns a named list with properties of the requested product.

Author(s)

Pepijn de Vries

See Also

Other product-functions: [cms_cite_product\(\)](#), [cms_product_details\(\)](#), [cms_product_metadata\(\)](#), [cms_product_services\(\)](#), [cms_products_list\(\)](#), [copernicus_cite_product\(\)](#), [copernicus_product_metadata\(\)](#), [copernicus_products_list\(\)](#)

Examples

```
## Not run:
copernicus_product_details("GLOBAL_ANALYSISFORECAST_PHY_001_024")

copernicus_product_details(
  product = "GLOBAL_ANALYSISFORECAST_PHY_001_024",
  layer   = "cmems_mod_glo_phy-thetao_anfc_0.083deg_P1D-m",
  variable = "thetao"
)

## End(Not run)
```

`copernicus_product_metadata`

Obtain meta data for a specific Copernicus marine product

Description

[Deprecated] Deprecated. Use [cms_product_metadata\(\)](#) instead.

Usage

```
copernicus_product_metadata(product)
```

Arguments

product	An identifier (type character) of the desired Copernicus marine product. Can be obtained with copernicus_products_list .
---------	------------------------------------------------------------------------------------------------------------------------------------------

Details

Collect meta information, such as vocabularies used, for specific Copernicus marine products

Value

Returns a named list with info about the requested product. Returns NULL when contacting Copernicus fails.

Author(s)

Pepijn de Vries

See Also

Other product-functions: [cms_cite_product\(\)](#), [cms_product_details\(\)](#), [cms_product_metadata\(\)](#), [cms_product_services\(\)](#), [cms_products_list\(\)](#), [copernicus_cite_product\(\)](#), [copernicus_product_details\(\)](#), [copernicus_products_list\(\)](#)

Examples

```
## Not run:
copernicus_product_metadata("GLOBAL_ANALYSISFORECAST_PHY_001_024")

## End(Not run)
```

copernicus_product_services

Obtain available services for a specific Copernicus marine product

Description

[Deprecated] Obtain an overview of services provided by Copernicus for a specific marine product.

Usage

```
copernicus_product_services(product)
```

Arguments

product	An identifier (type character) of the desired Copernicus marine product. Can be obtained with copernicus_products_list .
---------	------------------------------------------------------------------------------------------------------------------------------------------

Value

Returns a tibble with a list of available services for a Copernicus marine product

Author(s)

Pepijn de Vries

Examples

```
## Not run:
copernicus_product_services("GLOBAL_ANALYSISFORECAST_PHY_001_024")

## End(Not run)
```

`copernicus_wms2geotiff`*Extract and store WMS as a geo-referenced TIFF*

Description

[Deprecated] This function interacts with deprecated Copernicus Marine Services. It will become `.Defunct()` in future versions. Extract and store imagery from a Copernicus WMS as a geo-referenced TIFF.

Usage

```
copernicus_wms2geotiff(  
  product,  
  layer,  
  variable,  
  region,  
  destination,  
  width,  
  height  
)
```

Arguments

<code>product</code>	An identifier (type character) of the desired Copernicus marine product. Can be obtained with <code>copernicus_products_list</code> .
<code>layer</code>	The name of a desired layer within a product (type character). Can be obtained with <code>copernicus_product_details</code> .
<code>variable</code>	The name of a desired variable in a specific layer of a product (type character). Can be obtained with <code>copernicus_product_details</code> .
<code>region</code>	Specification of the bounding box as a vector of numerics WGS84 lat and lon coordinates. Should be in the order of: xmin, ymin, xmax, ymax.
<code>destination</code>	File name for the geo-referenced TIFF.
<code>width</code>	Width in pixels of the TIFF image.
<code>height</code>	Height in pixels of the TIFF image.

Details

A Web Map Service (WMS) cannot be plotted directly (base, ggplot2 and/or lattice). For that purpose you need to extract and download a specific region in a format that can be handled by plots. You can use this function to store a subset of a WMS map as a geo-referenced TIFF file.

Value

Stores the file as `destination` and returns invisible NULL

Note

WMS functions don't work on systems that don't support GDAL utils

Author(s)

Pepijn de Vries

See Also

Other wms-functions: [addCopernicusWMSTiles\(\)](#), [copernicus_wms_details\(\)](#)

Examples

```
## Not run:
destination <- tempfile("wms", fileext = ".tiff")
copernicus_wms2geotiff(
  product = "GLOBAL_ANALYSISFORECAST_PHY_001_024",
  layer = "cmems_mod_glo_phy-thetao_anfc_0.083deg_P1D-m",
  variable = "thetao",
  region = c(-1, 50, 7, 60),
  destination = destination,
  width = 1920,
  height = 1080
)

## End(Not run)
```

copernicus_wms_details

Obtain a WMS entry for specific Copernicus marine products

Description

[Deprecated] Web Map Services are not available for all products and layers. Use this function to obtain URLs of WMS services if any.

Usage

```
copernicus_wms_details(product, layer, variable)
```

Arguments

product	An identifier (type character) of the desired Copernicus marine product. Can be obtained with copernicus_products_list .
layer	The name of a desired layer within a product (type character). Can be obtained with copernicus_product_details .
variable	The name of a desired variable in a specific layer of a product (type character). Can be obtained with copernicus_product_details .

Value

Returns a tibble with WMS URLs and descriptors for the specified product.

Note

WMS functions don't work on systems that don't support GDAL utils

Author(s)

Pepijn de Vries

See Also

Other wms-functions: [addCopernicusWMSTiles\(\)](#), [copernicus_wms2geotiff\(\)](#)

Examples

```
## Not run:
copernicus_wms_details(
  product = "GLOBAL_ANALYSISFORECAST_PHY_001_024",
  layer   = "cmems_mod_glo_phy-thetao_anfc_0.083deg_P1D-m",
  variable = "thetao"
)

## End(Not run)
```

Index

- * **product-functions**
 - cms_cite_product, 4
 - cms_product_details, 10
 - cms_product_metadata, 11
 - cms_product_services, 12
 - cms_products_list, 9
 - copernicus_cite_product, 14
 - copernicus_product_details, 20
 - copernicus_product_metadata, 21
 - copernicus_products_list, 19
- * **stac-functions download-functions**
 - cms_download_stac, 5
- * **wms-functions**
 - addCopernicusWMSTiles, 2
 - copernicus_wms2geotiff, 23
 - copernicus_wms_details, 24
- .Defunct(), 23
- addCmsWMTSTiles (cms_wmts_details), 12
- addCopernicusWMSTiles, 2, 24, 25
- cms_cite_product, 4, 9–12, 14, 20–22
- cms_download_stac, 5
- cms_download_subset, 6
- cms_download_subset(), 15
- cms_list_stac_files
 - (cms_download_stac), 5
- cms_list_stac_files(), 5
- cms_login, 8
- cms_login(), 18
- cms_product_details, 4, 5, 7, 9, 10, 10,
11–14, 20–22
- cms_product_metadata, 4, 9, 10, 11, 12, 14,
20–22
- cms_product_metadata(), 21
- cms_product_services, 4, 9–11, 12, 14,
20–22
- cms_products_list, 4, 5, 7, 9, 10–14, 20–22
- cms_stac_properties
 - (cms_download_stac), 5
- cms_wmts_details, 12
- cms_wmts_get_capabilities
 - (cms_wmts_details), 12
- copernicus_cite_product, 4, 9–12, 14,
20–22
- copernicus_download_motu, 15
- copernicus_ftp_get
 - (copernicus_ftp_list), 17
- copernicus_ftp_list, 17, 17
- copernicus_login, 18
- copernicus_product_details, 3, 4, 7, 9–15,
17, 20, 20, 22–24
- copernicus_product_metadata, 4, 9–12, 14,
20, 21, 21
- copernicus_product_services, 22
- copernicus_products_list, 3, 4, 9–12, 14,
15, 17, 19, 20–24
- copernicus_wms2geotiff, 3, 23, 25
- copernicus_wms_details, 3, 24, 24
- dplyr::tibble(), 5
- httr2::response(), 5
- leaflet::addWMSTiles(), 3, 13
- leaflet::leaflet(), 3, 13
- xml2::xml_new_document(), 11, 13